

New experimental proposal for
neutrino cross sections with J-PARC
neutrino beam,
WAGASCI

A. Minamino (Kyoto Univ.)

May 22, 2014

NuInt14 @ Surrey, UK


Outline

- Motivation
- Candidate site
- Detector configuration
- Goals
- MC study
- Test of the detector components
- Schedule

Water Grid And SCIntillator detector **WAGASCI**

H₂O/CH detector
(3D grid-like structure)

topview



Box for
Japanese sweets (Wagashi)



We have submitted a proposal of the project to J-PARC PAC as an independent test experiment from T2K.

Project members

A. Bonnemaïson, O. Drapier, O. Ferreira, M. Gonin, Th.A. Mueller, and B. Quilain

*Ecole Polytechnique, IN2P3-CNRS, Laboratoire Leprince-Ringuet, Palaiseau,
France*

I. Ayzenberg, A. Izmaylov, I. Karpikov, M. Khabibullin, A. Khotjantsev,
Y. Kudenko, S. Martynenko, A. Mefodiev, O. Mineev, T. Ovsjannikova,
S. Suvorov, and N. Yershov

*Institute for Nuclear Research of the Russian Academy of Sciences, Moscow,
Russia*

T. Hayashino, A.K. Ichikawa, A. Minamino, K. Nakamura, T. Nakaya, and
K. Yoshida

Kyoto University, Department of Physics, Kyoto, Japan

Y. Seiya, K. Wakamatsu, and K. Yamamoto

Osaka City University, Department of Physics, Osaka, Japan

N. Chikuma, T. Koga, and M. Yokoyama

University of Tokyo, Department of Physics, Tokyo, Japan

Y. Hayato

*University of Tokyo, Institute for Cosmic Ray Research, Kamioka Observatory,
Kamioka, Japan*

Motivation

- T2K have non-canceling systematic errors on neutrino cross sections because of different primary nuclear targets^(*) of Super-K (H_2O) and T2K off-axis near detector, ND280 (CH).

Uncertainties on the predicted number of signal ν events

ν_e appearance analysis (PRL 112, 061802 (2014))

Error source [%]	$\sin^2 2\theta_{13} = 0.1$
Beam flux and near detector (without ND280 constraint)	2.9 (25.9)
Uncorrelated ν interaction	7.5
Far detector and FSI + SI + PN	3.5
Total	8.8

ν_μ disappearance analysis (PRL 112, 181801 (2014))


Source of uncertainty (number of parameters)	$\delta n_{SK}^{\text{exp}} / n_{SK}^{\text{exp}}$
ND280-independent cross section (11)	4.9%
Flux and ND280-common cross section (23)	2.7%
SK detector and FSI + SI systematics (7)	5.6%
$\sin^2(\theta_{13})$, $\sin^2(\theta_{12})$, Δm_{21}^2 , δ_{CP} (4)	0.2%
Total (45)	8.1%

(*) The ND280 has water target regions, and there are ongoing efforts to measure neutrino cross sections on water.

Motivation (continue)



- Acceptance of the ND280 is smaller than that of Super-K ($= 4\pi$).
 - T2K need to rely on external data sets (MiniBooNE, etc.).

N_μ CCQE double differential cross section
discrepancies between DATA and Model



Motivation (continue)



- We have measured an Fe to CH neutrino cross section ratio with an accuracy of **2.7%** using the T2K on-axis near detector, INGRID. (T. Kikawa's talk @ NuInt14 on May 19)



$$\frac{\sigma_{CC}^{Fe}}{\sigma_{CC}^{CH}} = 1.047 \pm 0.007 (stat.)_{-0.027}^{+0.028} (syst.)$$

Candidate site

- The B2 floor of the T2K near detector hall as a test facility of neutrino beam
 - Off-axis angle ~ 1.6 degree
 - Neutrino energy spectrum is similar to the ND280/Super-K.



Detector configuration

- WAGASCI detector + muon range detectors (MRDs)
 - MRDs are located 50cm away from the WAGASCI detector to identify the charged particle directions from hit-timing diff. between the two detectors.



Top view
Front VETO

↓ ν beam

MRDs



Side (x 2 or x 4)

Downstream (x 1)




WAGASCI detector

- Dimensions
 - 100cm x 100cm in section and 200cm along the beam direction
 - H₂O/CH target mass is ~2 ton in total. (Total weight ~ 3 ton.)
- 3D grid-like structure (x, y, grid layers + WLS fibers + MPPCs)
 - **4 π angular acceptance** for charged particles
 - 2.5cm grid spacing enables us to reconstruct short tracks originated from protons and charged pions with high efficiency.
 - Thin plastic scintillator bars (thickness ~ 0.3cm) will be used for the detector to increase the mass ratio of H₂O (signal) to CH (background).
 - The WAGASCI detector can be made possible if we have high light yield from the thin scintillator bars in water with the MPPC readout.



Advantages of the WAGASCI detector

- 4π angular-acceptance
- $\text{H}_2\text{O}(\text{signal}):\text{CH}(\text{BG}) = 70:30$
 - T2K ND280: $\text{H}_2\text{O}:\text{CH} = 46:54$
- Similar detector systematics for $\text{H}_2\text{O}/\text{CH}$ measurements
 - Each cell of the 3D grid is filled with hydrocarbon blocks in the CH target regions.




muon range detectors (MRDs)

- Side MRDs

- Dimensions $\sim 300\text{cm} \times 200\text{cm} \times 100\text{cm}$
- 14 tracking planes and 12 steel plates
 - Weight of a steel plate: 1.4 ton
 - Weight of a tracking plane: 160kg
- Total weight for each: ~ 21 tons
- Can measure p_μ up to ~ 1 GeV/c

- Downstream MRD


- Dimensions $\sim 350\text{cm} \times 200\text{cm} \times 220\text{cm}$
- 32 tracking planes and 30 steel plates
 - Weight of a steel plate: 1.7 ton
 - Weight of a tracking planes: 190kg
- Total weight: ~ 60 tons
- Can measure p_μ up to ~ 2 GeV/c




Downstream muon detector

- Another option for the downstream muon detector
 - We are considering the possibility to reuse the detector which is developed for muon radiography as the downstream muon detector.
 - Scintillator tracking planes + magnetic field using permanent magnets
 - Advantages
 - Can identify muon charges (Good for anti- ν beam data.)
 - Can measure p_μ up to 5 GeV/c


Permanent Toroid Magnet



Sketch of the toroid magnet



Simulation of the field strength




Goals

- H₂O to CH cross section ratios with 3% accuracy
 - Neutrino interaction models predict that the target dependence between H₂O and CH is small, but no high precision measurement so far.
 - Test the correctness of the target dependence in the models. Then, constrain the target-dependent neutrino cross section errors by the ND280 measurement.
 - The analysis technique is established in the INGRID measurement.
 - CC-inclusive channel. Then, exclusive channels.
- Cross sections on H₂O and CH with 10% accuracy.
 - Neutrino flux uncertainties are dominant errors.
 - Double differential cross sections for $(T_\mu, \cos\theta_\mu)$
 - CC-inclusive channel. Then, exclusive channels.

MC study (CC-inclusive)


- Neutrino flux prediction
 - Hadron production (NA61@CERN) & Proton/ ν beam monitoring
- Neutrino interaction generator: NEUT
- Detector MC: Geant4
 - Geometry in the MC is slightly different from the one in p. 9. (Better performance is expected by adapting the geometry in p.9 to the MC.)

A event display of the WAGASCI detector (CCQE event)



MC study (CC-inclusive) (Continue.)


- Event selection
 - Reconst. tracks/vertices in the WAGASCI detector and the MRDs.
 - Require a track to be matched between two detectors and be stopped in the MRDs.
 - Select a long muon track from CC interaction.
 - Remove charged particle BGs from VETO layer hits & TOF ($t_1 < t_2$).
 - Vertices are in the fiducial volume of the WAGASCI detector.




MC study (CC-inclusive) (Continue.)

- BGs originate from neutrino interactions in the material surrounding the WAGASCI detector
 - Dominant BG source is found to be neutral particles (n, γ) from neutrino interactions in the walls of the near detector hall.

Events with a matched track
in the downstream MRD




Events with a matched track
in the side MRDs



BG contamination can be reduced to a **5%** level, if events with ≥ 4 (2) penetrating iron layers in the downstream (side) MRDs are selected.

MC study (CC-inclusive) (Continue.)

- Selected interaction types after applying the selection on # of penetrating iron layers in the MRDs



Purity of CC-inclusive interactions is **92%**

- The expected # of ν_μ CC event candidates in the WAGASCI detector is 42000 in total in 1×10^{21} POT of ν beam data.
 - Stat. error will be less than 1%.

MC study (CC-inclusive) (Continue.)

- Analysis strategy
 - Flux averaged CC-inclusive is calculated with background subtraction and efficiency correction.

$$\sigma_{CC} = \frac{N_{sel} - N_{BG}}{\Phi T \epsilon_{CC}}$$

N_{sel} : Number of selected events (data)

N_{BG} : Number of selected BG events (MC)

Φ : Integrated ν_{μ} flux (MC)


T : Number of target nucleons

ϵ_{CC} : Detection efficiency of CC events (MC)


- This calculation is applied to the H₂O target regions and the CH target regions to measure $\sigma_{CC}^{H_2O}$ and σ_{CC}^{CH} .
- Then, $\sigma_{CC}^{H_2O} / \sigma_{CC}^{CH}$ is calculated.
 - The dominant systematic error, the neutrino flux error is canceled.

Test of the detector components

- Long-term durability test of scintillator bars & WLS fibers in water



Light yield for cosmic ray muons





- Scintillator bars: T2K INGRID type
- WLS fiber: Kuraray Y11
- MPPCs: T2K ND type (1.3 x 1.3 mm²), $V_{\text{over}} = 1.1\text{V}$

Stable for 180 days

Test of the detector components (Continue.)

- Performance of new MPPCs developed by Hamamatsu
 - Low noise ($\sim 1/10$ compared to T2K version)
 - Much less after pulse
 - Wider operation voltage
 - Low cross-talk (optional)
- Improved wafer and processing
- Special structure





Test of the detector components (Continue.)

- Performance of new MPPCs developed by Hamamatsu

- Low noise ($\sim 1/10$ compared to T2K version)
- Much less after pulse
- Wider operation voltage
- Low cross-talk (optional)

} Improved wafer and processing




→ Special structure



We will operate the new MPPC at a high V_{over} . (High PDE is achieved.)

Test of the detector components (Continue.)

- We have tested 3mm-thick scintillator bars which have the groove/slits for the 3D grid-like structure by using positron beam at Tohoku Univ. on May, 2014.
 - Fermi-lab's scinti. (maybe be degraded)
 - MPPCs: T2K ND type
- Check items
 - Hit efficiency for MIP
 - Light yield for MIP
 - Optical cross talks



Schedule

- May – Jun., 2014: Neutrino beam measure. w/ an existing INGRID mod. at the candidate site.
 - BG study at the candidate site.
- Oct., 2014: 2nd beam test at Tohoku Univ.
 - Finish the performance test of the detector components (Scintillator bars, WLS fibers, MPPCs, ...)
 - Test a prototype of the WAGASCI detector (~ 100ch)
- Dec., 2014: Completion of the detector design
- Jan. – May, 2015: Order/delivery of the detector components
- Jun. – Oct., 2015: Detector construction/installation
- Nov., 2015: Detector commissioning
- **Dec., 2015: Start operation**

Summary

- We propose a test experiment, **WAGASCI**, to develop a 3D grid-like neutrino detector with a water target at the near detector hall of J-PARC neutrino beamline.
- Goals of the project
 - Measure the H₂O to CH charged current cross section ratio with 3% precision.
 - Double differential cross sections on H₂O and CH with 10% precision.
- MC studies/test of the detector components are ongoing.
- Start operation on Dec., 2015.

Backup